

Specifications:  
Rating:  
Current Rating:0.5 Amp  
Voltage Rating:50V AC/DC  
Operating Temperature Range:-40°~+105°C  
Max Processing Temp.:260°C for 5 Seconds

Electrical:  
Contact resistance:40m Ohm Max  
Insulator resistance:500M ohm min.  
Withstanding Voltage:200V AC/Minute

Material And Finish:  
Housing:LCP UL94V-0 Natural  
Cover(ZIF):LCP UL94V-0 Black  
Terminal:Phosphor Bronze,  
Plating:Tin plated Over Nickel

| No.of | A     | B     | C     |
|-------|-------|-------|-------|
| 04    | 3.00  | 5.10  | 6.00  |
| 05    | 4.00  | 6.10  | 7.00  |
| 06    | 5.00  | 7.10  | 8.00  |
| 07    | 6.00  | 8.10  | 9.00  |
| 08    | 7.00  | 9.10  | 10.00 |
| 09    | 8.00  | 10.10 | 11.00 |
| 10    | 9.00  | 11.10 | 12.00 |
| 11    | 10.00 | 12.10 | 13.00 |
| 12    | 11.00 | 13.10 | 14.00 |
| 13    | 12.00 | 14.10 | 15.00 |
| 14    | 13.00 | 15.10 | 16.00 |
| 15    | 14.00 | 16.10 | 17.00 |
| 16    | 15.00 | 17.10 | 18.00 |
| 17    | 16.00 | 18.10 | 19.00 |
| 18    | 17.00 | 19.10 | 20.00 |
| 19    | 18.00 | 20.10 | 21.00 |
| 20    | 19.00 | 21.10 | 22.00 |
| 21    | 20.00 | 22.10 | 23.00 |
| 22    | 21.00 | 23.10 | 24.00 |
| 23    | 22.00 | 24.10 | 25.00 |
| 24    | 23.00 | 25.10 | 26.00 |
| 25    | 24.00 | 26.10 | 27.00 |
| 26    | 25.00 | 27.10 | 28.00 |
| 27    | 26.00 | 28.10 | 29.00 |
| 28    | 27.00 | 29.10 | 30.00 |
| 29    | 28.00 | 30.10 | 31.00 |
| 30    | 29.00 | 31.10 | 32.00 |
| 31    | 30.00 | 32.10 | 33.00 |
| 32    | 31.00 | 33.10 | 34.00 |
| 33    | 32.00 | 34.10 | 35.00 |
| 34    | 33.00 | 35.10 | 36.00 |
| 35    | 34.00 | 36.10 | 37.00 |



PART NO. :  
FPC228N0XX-CTX-CF1337  
R:Tape/Reel Packing

FFC/FPC Dimension(Thickness 0.30 mm)

|                                                                                                                                 |                                                      |                                |                                                       |  |                      |     |             |                           |
|---------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------|--------------------------------|-------------------------------------------------------|--|----------------------|-----|-------------|---------------------------|
| <br>承洧科技股份有限公司<br>Cherng Wee Technology Corp. | DESCRIPTION(内容):<br><b>FPC 1.0mm SMT TYPE (RoHS)</b> | DRAWN(製圖):<br><b>HUANG</b>     | GENERAL TOLERANCE:<br>(公差)<br>. X ±0.20<br>. XX ±0.10 |  | REV:<br><b>R0</b>    | REV | DESCRIPTION | DATE<br><b>2019.02.19</b> |
|                                                                                                                                 | PART NO:<br>(料號) <b>FPC228N0XX-CTR-CF1337</b>        | CHECKED(確認):<br><b>TERESA</b>  |                                                       |  | UNIT:<br><b>mm</b>   |     |             |                           |
|                                                                                                                                 | DWG NO(圖號): <b>0010131-XX2323</b>                    | APPROVAL(核准):<br><b>JOHNNY</b> | SCALE(比例):<br><b>FREE</b>                             |  | SIZE:<br><b>A4</b>   |     |             |                           |
|                                                                                                                                 |                                                      |                                |                                                       |  | SHEET:<br><b>1/1</b> |     |             |                           |
|                                                                                                                                 |                                                      |                                |                                                       |  |                      |     |             |                           |

A

B

C

D

E

CF13