


A

B


C

D

E



P/N: CBTB-05M-AXXX



NOTE

A. Material:




1. Housing : Nylon-9T Halogen Free UL94V-0,Black
2. Contact : Copper Alloy
3. Plating : Gold Plating.

B.Temperature: -20°C to +105°C


C.Electrical:

1. Voltage : 50V.
2. Current : 0.5A.
3. Contact Resistance : 40mΩ max.
4. Dielectric Withstanding Voltage : 500V AC / 1 min.
5. Insulation Resistance : 100MΩ min.

D.Available Pins : 20~100 Contacts



P/N: CBTB-05F-BXXX



DESCRIPTION(内容):

0.50mm (0.0197") Pitch Board To Board
connector Male+Female H=4.65mm
(RoHS)

PART NO:
(料 號)

DWG NO(圖號): 0545

DRAWN(製圖):

GONG

CHECKED(確認):

TERESA

APPROVAL(核准):

JOHNNY

GENERAL TOLERANCE:
(公差)

.X ±0.30
.XX ±0.20
.XXX ±0.10

SCALE(比例):

FREE



REV:
R2

UNIT:
mm

SIZE:

A4

SHEET:

1/3

REV

R0

R1

R2

R3

DESCRIPTION

RELEASE

2014年改為無鹵料/圖面更新

變更Ⓐ尺寸(原:4.50)

DATE

2008.05.14

2014.09.16

2017.03.29

A

B

C

D

E



A

B

C

D

E



NOTE

A. Material:



1. Housing : Nylon-9T Halogen Free
UL94V-0, Black
2. Contact : Copper Alloy
3. Plating : Gold Plating.

B. Temperature: -20° C to +105° C


C. Electrical:

1. Voltage : 50V.
2. Current : 0.5A.
3. Contact Resistance : 40mΩ max.
4. Dielectric Withstanding Voltage :
500V AC / 1 min.
5. Insulation Resistance : 100MΩ min.

D. Available Pins : 20~100 Contacts



PCB Layout For Surface Mounting



DESCRIPTION(内容):

0.50mm (0.0197") Pitch Board To Board
Male connector A-type H=2.40mm(RoHS)

PART NO:
(料 號) CBTB-05M-AXXX

DWG NO(圖號): BTB-05M-AXXX

DRAWN(製圖):

GONG

CHECKED(確認):

TERESA

APPROVAL(核准):

JOHNNY

GENERAL TOLERANCE:
(公差)

.X ±0.30
.XX ±0.20
.XXX ±0.10

SCALE(比例):

FREE



REV:

R4

UNIT:

mm

SIZE:

A4

SHEET:

2/3

REV

R0

R1

R2

R3

R4

DESCRIPTION

RELEASE
補充Layout圖示定位柱尺寸

2014年改為無鹵料/圖面更新

修正塑膠外觀

圖面更新

DATE

2008.05.14
2011.01.18

2014.09.16

2015.01.27

2017.03.28

A

B

C

D

E



A

B

C

D

E



NOTE

A. Material:

1. Housing : Nylon-9T Halogen Free
UL94V-0,Black

2. Contact : Copper Alloy

3. Plating : Gold Plating.

B.Temperature: -20°C to +105°C

C.Electrical:

1. Voltage : 50V.



2. Current : 0.5A.

3. Contact Resistance : 40mΩ max.


4. Dielectric Withstanding Voltage :
500V AC / 1 min.

5. Insulation Resistance : 100MΩ min.

D.Available Pins : 20~100 Contacts



PCB Layout For Surface Mounting

承洧科技股份有限公司
Cherng Wee Technology Corp.

DESCRIPTION(內容):

0.50mm (0.0197") Pitch Board To Board
Female connector B-type H=3.70mm
(RoHS)PART NO:
(料 號)

CBTB-05F-BXXX

DWG NO(圖號):

BTB-05F-BXXX

DRAWN(製圖):

GONG

CHECKED(確認):

TERESA

APPROVAL(核准):

JOHNNY

GENERAL TOLERANCE:

(公差)

.X ±0.30

.XX ±0.20

.XXX ±0.10

SCALE(比例):

FREE



REV:

R5

UNIT:

mm

SIZE:

A4

SHEET:

3/3

REV

R0

R1

R2

R3

R4

R5

DESCRIPTION

RELEASE
補充Layout圖示定位柱尺寸
2014年改為無齒料/圖面更新
修正塑膠外觀

新增 ① 尺寸

變更 ① 尺寸(原:φ0.70±0.2)

DATE

2008.05.14

2011.01.13

2014.09.16

2015.01.29

2015.07.09

2017.03.29

A

B

C

D

E