

A

B

C

D

E

1

1

2

2

3

3

Note:

1.Plastic Material: PBT&Glass-Fiber,UL94V-0.

2.Contacts Material: Copper Alloy.

3.Plating: 30-50u" nickel plating under,au plated on gold plating area.

4.Operating Temperature: -20℃ ~ 85℃.

5.Current Rating: 1.5Amp.

6.Insulation Resistance: 1000MΩ Min.

7.Withstanding Voltage: 500V AC for 1 minute.

8.Contact Resistance: 30mΩ Max.



PIN數	Dim	PIN數	Dim
	A		A
06	12.1	28	40.1
08	14.7	30	42.6
10	17.3	32	45.1
12	19.8	34	47.7
14	22.3	40	55.6
16	24.8	44	60.5
18	27.5	50	68.4
20	29.9	60	81.2
24	34.9	64	86.2
26	37.6		

DESCRIPTION(內容):

FC SOKCET 2.54mm
IDC 三件式 有凸點(RoHS)

PART NO:
(料 號) **CFC010XX**

DWG NO(圖號): **XIDC-0001**

DRAWN(製圖):

GONG

CHECKED(確認):

TERESA

APPROVAL(核准):

JOHNNY

GENERAL TOLERANCE:

(公差)

.00 ±0.20

SCALE(比例):

FREE

REV:

R4

UNIT:

mm

SIZE:

A4

SHEET:

1/1

REV

R0**R1****R2****R3****R4**

DESCRIPTION

補充中蓋尺寸

補充(A)尺寸

變更端子材質旭數

圖面更新

DATE

2006.11.10
2008.01.24**2008.02.02****2016.05.25****2017.03.07**

A

B

C

D

E