

A

B

C

D

E

## Specifications:

- Material: Polyester, UL 94V-0
- Voltage Rating: 250V
- Current Rating: 5A
- Withstand Voltage: 1500V AC/Minute
- Insulation Resistance: 1000M $\Omega$  min.
- Temperature Range: -25°C~+85°C
- Contact Resistance: Initial value/10m $\Omega$  max.  
After environmental testing/20m $\Omega$  max.
- Standard Color: Black

### Dimensional & Ordering Information:

| Circuits | Part No        | Dimensions mm |      |
|----------|----------------|---------------|------|
|          |                | A             | B    |
| 02       | CMF-H300M-2X01 |               | 4.0  |
| 04       | CMF-H300M-2X02 | 3.00          | 7.0  |
| 06       | CMF-H300M-2X03 | 6.00          | 10.0 |
| 08       | CMF-H300M-2X04 | 9.00          | 13.0 |
| 10       | CMF-H300M-2X05 | 12.00         | 16.0 |
| 12       | CMF-H300M-2X06 | 15.00         | 19.0 |
| 14       | CMF-H300M-2X07 | 18.00         | 22.0 |
| 16       | CMF-H300M-2X08 | 21.00         | 25.2 |
| 18       | CMF-H300M-2X09 | 24.00         | 28.2 |
| 20       | CMF-H300M-2X10 | 27.00         | 31.2 |
| 22       | CMF-H300M-2X11 | 30.00         | 34.2 |
| 24       | CMF-H300M-2X12 | 33.00         | 37.2 |



A

B

C

D

E



承洧科技股份有限公司  
Cherng Wee Technology Corp.

#### DESCRIPTION(內容):

3.0mm (.118") Micro-Fit connector  
(RoHS)

PART NO:  
(料 號)

CMF-H300M-2xXX

DWG NO(圖號): 5750-H

#### DRAWN(製圖):

GONG

#### CHECKED(確認):

MANDY

#### APPROVAL(核准):

JOHNNY

#### GENERAL TOLERANCE:

(公差)

.00  $\pm 0.15$   
.0  $\pm 0.25$

#### SCALE(比例):

FREE



#### REV:

R1

#### UNIT:

mm

#### SIZE:

A4

#### SHEET:

1/1

#### REV

R0

R1

R2

R3

#### DESCRIPTION

RELEASE

2014年8月料號P數編碼統一兩碼

#### DATE

2009.06.06

2015.01.21