



P. C. B Hole Layout

Specifications

Current Rating	: 0.8 Amp
Insulator Resistance	: 900 Megohms Min.
Dielectric Withstanding	: AC 500 V
Operating Temperature	: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$
Contact Material	: Copper Alloy
Insulator Material	: High Temperature Thermoplastic. UL 94V-0
Standard Finish	: Nylon-6T/LCP
Standard	: Tin, Gold Plated
	: Gold Flash all over

How to order

Series	Connector Type	Contact Plating	Material	Pin Length mm	Number of Contacts
<u>P702</u>	- <u>X</u>	<u>X</u>	<u>X</u>	- <u>A</u> / <u>B</u>	- <u>X</u> <u>X</u>
(Pin Header Series Row) P702 (H:1.0 W:1.27)	S: Straight Type ...	G: Gold Flash T: Tin Plated A: 10U" Gold B: 15U" Gold C: 20U" Gold © Duplex Plating D: Gold Flash/Tin (Standard: G)	N: Nylon-6T C: LCP (Standard: N)	A (033) B (033) (If you desire on other length, by marking put desired in the A/B)	(01 TO 50 Contacts)

Dim(3.3/3.3):

A: _____ B: _____



CHERNG WEEI

DESCRIPTION(内容):

1.0mm Pin Header H:1.0 180° □=0.30 (RoHS)

PART NO:
(料 號)

DWG NO(圖號):

DRAWN(製圖):

CHECKED(確認):

APPROVAL(核准):

GENERAL TOLERANCE:
(公差)

.X .XXXX
.XX .X°
.XXX .XX°

SCALE(比例):
1:XX



REV:
A/1

UNIT:
mm

SIZE:
A4

SHEET:
1/1

REV

0

1

2

3

DESCRIPTION

DATE

A

B

C

D

E

FILE NO: CWJ-4E-09